



User's Guide

bintec R1200 / R1200w(u) / R3000 / R3000w / R3400 / R3800(wu)

BRRP

Copyright © December 12, 2006 Funkwerk Enterprise Communications GmbH
Version 3.0

Purpose	This document is part of the user's guide to the installation and configuration of bintec gateways running software release 7.4.10 or later. For up-to-the-minute information and instructions concerning the latest software release, you should always read our Release Notes , especially when carrying out a software update to a later release level. The latest Release Notes can be found at www.funkwerk-ec.com .		
Liability	While every effort has been made to ensure the accuracy of all information in this manual, Funkwerk Enterprise Communications GmbH cannot assume liability to any party for any loss or damage caused by errors or omissions or by statements of any kind in this document and is only liable within the scope of its terms of sale and delivery. The information in this manual is subject to change without notice. Additional information, changes and Release Notes for bintec gateways can be found at www.funkwerk-ec.com .		
	As multiprotocol gateways, bintec gateways set up WAN connections in accordance with the system configuration. To prevent unintentional charges accumulating, the operation of the product should be carefully monitored. Funkwerk Enterprise Communications GmbH accepts no liability for loss of data, unintentional connection costs and damages resulting from unsupervised operation of the product.		
Trademarks	bintec and the bintec logo are registered trademarks of Funkwerk Enterprise Communications GmbH. Other product names and trademarks mentioned are usually the property of the respective companies and manufacturers.		
Copyright	All rights are reserved. No part of this publication may be reproduced or transmitted in any form or by any means – graphic, electronic, or mechanical – including photocopying, recording in any medium, taping, or storage in information retrieval systems, without the prior written permission of Funkwerk Enterprise Communications GmbH. Adaptation and especially translation of the document is inadmissible without the prior consent of Funkwerk Enterprise Communications GmbH.		
Guidelines and standards	bintec gateways comply with the following guidelines and standards: R&TTE Directive 1999/5/EG CE marking for all EU countries and Switzerland You will find detailed information in the Declarations of Conformity at www.funkwerk-ec.com .		
How to reach Funkwerk Enterprise Communications GmbH	<table border="1"> <tr> <td>Funkwerk Enterprise Communications GmbH Suedwestpark 94 D-90449 Nuremberg Germany Telephone: +49 180 300 9191 0 Fax: +49 180 300 9193 0 Internet: www.funkwerk-ec.com</td><td>Bintec France 6/8 Avenue de la Grande Lande F-33174 Gradignan France Telephone: +33 5 57 35 63 00 Fax: +33 5 56 89 14 05 Internet: www.bintec.fr</td></tr> </table>	Funkwerk Enterprise Communications GmbH Suedwestpark 94 D-90449 Nuremberg Germany Telephone: +49 180 300 9191 0 Fax: +49 180 300 9193 0 Internet: www.funkwerk-ec.com	Bintec France 6/8 Avenue de la Grande Lande F-33174 Gradignan France Telephone: +33 5 57 35 63 00 Fax: +33 5 56 89 14 05 Internet: www.bintec.fr
Funkwerk Enterprise Communications GmbH Suedwestpark 94 D-90449 Nuremberg Germany Telephone: +49 180 300 9191 0 Fax: +49 180 300 9193 0 Internet: www.funkwerk-ec.com	Bintec France 6/8 Avenue de la Grande Lande F-33174 Gradignan France Telephone: +33 5 57 35 63 00 Fax: +33 5 56 89 14 05 Internet: www.bintec.fr		

1	BRRP Menu	3
1.1	Terms and Definitions	4
1.2	Configuration of a Virtual Interface	6
2	Task Definition Submenu	9
3	Submenu Configuration	21
4	Monitoring Submenu	27
	Index: BRRP	31

1 BRRP Menu

The fields of the **BRRP** menu are described below.

R3000W Setup Tool	Funkwerk Enterprise Communications GmbH
[BRRP] : Redundancy Configuration	MyGateway
Watchdog Daemon	stopped
Task Definition >	
Configuration >	
Monitoring >	
SAVE	EXIT

This menu is for configuring the redundancy of your gateway.

BRRP (bintec Router Redundancy Protocol) is a bintec-specific implementation of VRRP (Virtual Router Redundancy Protocol). A router redundancy procedure is used mainly to protect the data of a service of a physical gateway in a **►► LAN** or WAN connected over Ethernet. This original gateway and all gateways that could potentially protect the transmission of the data of the service over the original gateway form a logical unit, which is called a “virtual router”. If the original gateway fails, another gateway that is part of the “virtual router” takes over the service of the original gateway.

Let us take the example of a simple scenario, in which gateway A provides **►► Internet** access for the hosts in a LAN. If this gateway fails, all the hosts that have statically configured routes and have not been configured to find alternative routes dynamically no longer have access to the Internet. To prevent this, gateway B starts offering all hosts in the LAN the service that gateway A previously performed. All the tasks of a “virtual router” and the switching of services from one gateway to the other are controlled by a router redundancy procedure.

The BRRP conforms to the specifications in RFC 2338 and the relevant Internet draft. (You will find the Internet drafts at <http://www.ietf.org/1id-abstracts.html>.)

The configuration of a “virtual router” is carried out in the following steps:

- Configuration of a virtual interface for integration into a “virtual router” (the configuration is made in the **ETHERNET UNIT X → VIRTUAL INTERFACES → ADD/EDIT** menu).
Administrative Multicasts (i.e. keepalives sent between the participating gateways) are sent over the physical interface. Virtual interfaces are therefore required for payload transmission on all gateways participating in the virtual router. These are assigned an identical virtual MAC address, which is called by the PC in the network. This means a backup gateway can take over the service if the original gateway fails.
- Configuration of the gateway for integration into a “virtual router” (configuration is made in the **BRRP → CONFIGURATION** menu).
This step includes defining the role of the virtual interface in the “virtual router” and the role of the master.
- Definition of the tasks that control the functions of the “virtual router” (configuration is made in the **BRRP → TASK DEFINITION** menu).
This step includes the configuration of the state change dependent on a state change of the master.

1.1 Terms and Definitions

A number of special terms are used to describe a “virtual router”.

The following terms are defined in the relevant RFC and the Internet draft.

Term	Meaning
VRRP Router	"A router that uses the Virtual Router Redundancy Protocol. It can be integrated into one or more "virtual routers"."

Term	Meaning
Virtual Router	"An abstract object controlled by the VRRP, which is used as default router for the hosts of a LAN. It comprises a Virtual Router Identifier (ID, editor's comment) and a group of associated IP addresses in a common LAN. A VRRP router can protect the data traffic of one or more "virtual routers"."
IP Address Owner	"The VRRP router that possesses the IP address(es) of the virtual router as real interface address(es). This is the router that – if active - answers packets for ►► ICMP pings, ►► TCP connections, etc. to one of these ►► IP addresses ." This means the router that possesses priority 255 is the "IP Address Owner"."
Primary IP Address	"An IP address that is selected from the group of real interface addresses. A possible algorithm option is the selection of the first address. VRRP advertisements are always sent with the primary IP address as source of the IP packet."
VRRP Advertisement	A keepalive that the master sends to the backup gateways to indicate his reachability.
Virtual Router Master	"The VRRP router that takes over forwarding the packets that have been sent to the IP addresses associated with the "virtual router". It is also responsible for answering ►► ARP (Address Resolution Protocol) requests for these IP addresses. Note that the "IP Address Owner" is always master if reachable."
Virtual Router Backup	"The group of VRRP routers that take over responsibility for forwarding the packets if the master fails."

Table 1-1: Terms for "virtual router"

1.2 Configuration of a Virtual Interface

The configuration of a virtual interface is carried out via the **ETHERNET UNIT X** menu in the **VIRTUAL INTERFACES** submenu. (It is not carried out in the **BRRP** menu). The following settings are obligatory if a virtual interface is to be configured as member in a “virtual router”:

- In the **ETHERNET UNIT X → VIRTUAL INTERFACES** menu, the value of the **IP CONFIGURATION** field must be set to *BRRP* or *BRRP over VLAN*.
- A virtual MAC address is obligatory. If you do not enter a MAC address, the entry is incomplete and cannot be saved. For the purpose of optimum interoperability and RFC conformity, the first 10 characters of the MAC address are suggested for you. You can edit these if required, but you are advised to use the predefined string. The last two (freely selectable) characters should indicate the Virtual Router ID (01, 02 ...).
- You must enter the addresses of the “virtual router” master as IP address and MAC address, regardless of whether you wish to use the virtual interface as master or backup.

Once you have configured the virtual interface, you can start the configuration in the **BRRP** menu.

The **BRRP** menu consists of the following field:

Field	Description
Watchdog Daemon	Here you activate (<i>running</i>) or deactivate (<i>stopped</i>) the Watchdog Daemon. The default value is <i>stopped</i> .

Table 1-2: **BRRP** menu field

The following **BRRP** submenus are used to define all the processes controlled by the BRRP:

- ***TASK DEFINITION***
- ***CONFIGURATION***
- ***MONITORING.***

2 Task Definition Submenu

The **TASK DEFINITION** submenu is described below.

R3000W Setup Tool				Funkwerk Enterprise Communications GmbH		
[BRRP] [TASKS] : Task List				MyGateway		
Task	Master		Slave			
ID	Protocol	Trigger	VR_ID/IFC	Protocol	Action	VR_ID/IFC
1	BRRP	any	1	BRRP	sync	1
ADD			DELETE		EXIT	



Note

TASK DEFINITION cannot be configured until you have created a virtual interface for BRRP in **ETHERNET → VIRTUAL INTERFACES** and participation in the virtual router has been defined in the **BRRP → CONFIGURATION** menu.

The Watchdog Daemon is configured in the **BRRP → TASK DEFINITION** menu, i.e. you define how the master state is determined and how state changes are handled.

The following criteria of the “virtual router” master are observed as trigger for actions by the backup (slave):

- Which IP address is to be checked for availability: This is defined first by the ID of the “virtual router” associated with a configuration that is set in **BRRP CONFIGURATION**, and second by the specification of an interface that refers to an entry in the **IFTABLE**.
- Which mechanism is used to determine the master state: This is either the BRRP advertisements of the master or the **OPERSTATUS** of the relevant interface.
- Which master state triggers the action configured for the backup.

The parameters of the “virtual router” backup action are defined under the following aspects:

- Which interface reacts to the master state configured as trigger: The interface can be specified by a Virtual Router ID (VRID) that is associated with a BRRP configuration or by an interface definition.
- The mechanism with which the backup reacts to the trigger: This can be the BRRP or the OperStatus of an interface.
- Which action the backup executes.

These parameters are specified in the **BRRP → TASK DEFINITION** menu.

A list of all configuration tasks is shown on opening the menu. Tasks can be added or edited in the **ADD/EDIT** menu (the screenshot contains example values).

R3000w Setup Tool		Funkwerk Enterprise Communications GmbH
[BRRP] [TASKS] [ADD] : Redundancy Task Definition		MyGateway
Task ID	1	
Master Interface Protocol	BRRP	
Master Action	any	
Master Interface	1	
Slave Interface Protocol	BRRP	
Slave Admin Action	sync	
Slave Interface	2	
SAVE		CANCEL

The **TASK DEFINITION → ADD/EDIT** menu consists of the following fields:

Field	Description
Task ID	The task IDs can be assigned as required. They are used for the logical arrangement of tasks but not for gateway-internal processes.

Field	Description
Master Interface Protocol	<p>Defines which mechanism is used for monitoring the master.</p> <p>Possible values:</p> <ul style="list-style-type: none">■ <i>BRRP</i> (default value with configured virtual router): The BRRP-specific state advertisements are used for determining the state of the master. The master sends advertisements as per its configuration in the CONFIGURATION menu.■ <i>IFC - operStatus</i> (default value without configured virtual router): The OPERSTATUS of MASTER INTERFACE is determined. The OPERSTATUS can be seen in the IFTABLE.

Field	Description
Master Action	<p>Defines the trigger of the task to be configured. The possible values depend on the selection in MASTER INTERFACE PROTOCOL:</p> <ul style="list-style-type: none"> ■ For MASTER INTERFACE PROTOCOL = BRRP: <ul style="list-style-type: none"> – <i>Initialize</i> (default value): The gateways associated with the virtual router are waiting for a startup event. – <i>Backup</i>: The availability of the master router is monitored. – <i>Master</i>: The virtual router is forwarding packets for IP addresses that are associated with this router. – <i>any</i>: MASTER ACTION = <i>Initialize</i>, <i>Backup</i> or <i>Master</i>. This option is only to be applied with SLAVE ACTION = <i>sync</i>. ■ For MASTER INTERFACE PROTOCOL = IFC-operStatus: <ul style="list-style-type: none"> – <i>up</i> (default value): The interface is active. – <i>down</i>: The interface is inactive. <p>For detailed information about the BRRP state see table “BRRP states,” on page 19.</p>
Virtual Router ID	<p>This field can only be edited if MASTER INTERFACE PROTOCOL is set to BRRP.</p> <p>Defines which interface is to be checked by selecting a Virtual Router ID (VRID). The Watchdog Daemon requests the detailed information entered in CONFIGURATION. The default value is 0 (if no VRID is defined) or the smallest VRID defined.</p>

Field	Description
Master Interface	<p>This field can only be edited if MASTER INTERFACE PROTOCOL is set to <i>IFC - operStatus</i>. Defines which BRRP interface is to be checked by selecting an interface name. The Watchdog Daemon requests details in the IFTABLE.</p>
Slave Interface Protocol	<p>Defines which mechanism the backup uses to react to the trigger:</p> <ul style="list-style-type: none"><li data-bbox="809 553 1315 680">■ <i>BRRP</i> (default value with configured virtual router): The backup changes to the BRRP state defined by the parameter selected in SLAVE ADMIN ACTION.<li data-bbox="809 706 1315 833">■ <i>IFC - adminStatus</i> (default value without configured virtual router): The backup changes to the ADMINSTATUS defined by the parameter selected in SLAVE ADMIN ACTION.

Field	Description
Slave Admin Action	<p>The following values are possible, depending on the trigger mechanism selected in SLAVE INTERFACE PROTOCOL:</p> <ul style="list-style-type: none"> ■ <i>up</i>: <ul style="list-style-type: none"> – For <i>BRRP</i> this means that the interface of the BRRP gateway in the “virtual router” is activated. It changes to the initial state (default value). – For <i>IFC - adminStatus</i> this means that the router interface SLAVE INTERFACE changes to <i>up</i>. ■ <i>down</i>: <ul style="list-style-type: none"> – For <i>BRRP</i> this means that the interface of the BRRP gateway in the “virtual router” is deactivated. – For <i>IFC - adminStatus</i> this means that the router interface SLAVE INTERFACE changes to <i>down</i>. ■ <i>none</i>: <ul style="list-style-type: none"> – For <i>IFC - adminStatus</i> only: Means that no action is triggered (default value). ■ <i>sync</i>: <ul style="list-style-type: none"> – only for SLAVE INTERFACE PROTOCOL = BRRP The gateway synchronizes its BRRP state according to the state of the other gateways participating in the virtual router.

Field	Description
Virtual Router ID	<p>This field can only be edited if SLAVE INTERFACE PROTOCOL is set to <i>BRRP</i>.</p> <p>The backup searches the BRRP advertisements sent by the master to obtain information on whether the “virtual router” is to be started or stopped. This means a VRID must be defined. The default value is 0 or the smallest VRID defined.</p>
Slave Interface	<p>This field can only be edited if SLAVE INTERFACE PROTOCOL is set to <i>IFC - adminStatus</i>.</p> <p>The backup cannot determine if the “virtual router” is to be started or stopped. The BRRP interface must therefore be selected.</p>

Table 2-1: **TASK DEFINITION** menu fields

- BRRP states** The BRRP specifies three different possible states that BRRP routers can have. The behavior of the BRRP router changes according to the state. The various forms of behavior are very complex and have a large number of dependencies (especially in the master state).

The router has the following possible states and corresponding forms of behavior:

State	Behavior
Initialize	<p>The purpose of this state is to wait for a startup event. If the BRRP router is activated, it behaves as follows:</p> <ul style="list-style-type: none"> ■ If the local priority is 255: <ul style="list-style-type: none"> – the router sends a BRRP advertisement. – the router sends an additional ARP (Address Resolution Protocol) packet that contains the MAC address of the “virtual router” for each IP address connected to the “virtual router”. – the router sets the internal Advertisement Timer to the configured Advertisement Interval. – the router changes to the master state. ■ In all other cases: <ul style="list-style-type: none"> – the router sets the internal Master Down Timer to the calculated Master Down Interval. – the router changes to the backup state.

State	Behavior
Backup	<p>The purpose of the backup state is to monitor the availability and state of the master. A BRRP router behaves as follows in this state:</p> <ul style="list-style-type: none">■ It does not answer ARP requests for the IP addresses connected to the “virtual router”.■ It discards packets if these have a Destination Link Layer MAC address the same as the MAC address of the “virtual router”.■ It accepts no packets that are addressed to one or more IP address(es) connected to the “virtual router”.■ If the BRRP router is deactivated:<ul style="list-style-type: none">– it stops the internal Master Down Timer.– it changes to the initialize state.

State	Behavior
Master	<p>In the master state the router acts as forwarding router for the IP addresses connected to the “virtual router”. The BRRP router behaves as follows in this state:</p> <ul style="list-style-type: none"> ■ It answers ARP requests for IP addresses connected to the “virtual router”. ■ It forwards packets that have a Destination Link Layer MAC address the same as the MAC address of the “virtual router”. ■ It accepts no packets addressed to IP addresses connected to the “virtual router” if it is not the owner of the IP address. <p>If the BRRP router is deactivated:</p> <ul style="list-style-type: none"> ■ it stops the internal Advertisement Timer. ■ it sends an advertisement with priority = 0. ■ it changes to the initialize state. <p>If the internal Advertisement Timer starts:</p> <ul style="list-style-type: none"> ■ it sends an advertisement. ■ it resets the internal Advertisement Timer to the Advertisement Interval. <p>If an advertisement is received:</p> <ul style="list-style-type: none"> ■ if the priority in the advertisement is 0: <ul style="list-style-type: none"> – it sends an advertisement. – it resets the internal Advertisement Timer to the Advertisement Interval.

State	Behavior
Master (cont.)	<ul style="list-style-type: none">■ if the priority in the advertisement is higher than the local priority or the priority in the advertisement is the same as the local priority and the PRIMARY IP ADDRESS of the sender is higher than the local PRIMARY IP ADDRESS:<ul style="list-style-type: none">– it stops the internal Advertisement Timer.– it sets the internal Master Down Timer to the calculated Master Down Interval.– it changes to the backup state.■ if the priority in the advertisement is lower than the local priority:<ul style="list-style-type: none">– is discards the advertisement.

Table 2-2: **BRRP STATES**

3 Submenu Configuration

The **CONFIGURATION** submenu is described below.

R3000W Setup Tool					Funkwerk Enterprise Communications GmbH
[BRRP] [DAEMON] : Virtual Router List					MyGateway
VrID	Prio	State	Interface	IP-Address	MAC-Address
1	255	master	en1-0-1	192.168.1.254	00005e000101
2	255	slave	en1-3-1	172.16.1.254	00005e000102

ADD	DELETE	EXIT
-----	--------	------

The first step in the configuration of the processes controlled by BRRP is to define the participants in the “virtual router” in the **BRRP → CONFIGURATION** menu.

Opening the **CONFIGURATION** menu shows a list of the “virtual routers”.

Configuration is carried out in the **CONFIGURATION → ADD/EDIT** menu.

R3000W Setup Tool		Funkwerk Enterprise Communications GmbH
[BRRP] [DAEMON] [ADD] : Configure Virtual Router		MyGateway
Virtual Router ID	1	
Virtual Router State	down	
Priority	100	
Advertisement Interface	en1-0	
Virtual Interface	en1-0-1	
Master IP-Address	192.168.1.254	
MAC-Address	00005e000101	
Advertisement Interval	1	
Master Down Interval	3	
Pre-empt Mode	true	
Authentication Type	No Authentication	
Authentication Key		
SAVE	CANCEL	

The menu consists of the following fields:

Field	Description
Virtual Router ID	<p>Here you select the Virtual Router Identifier (VRID).</p> <p>The VRID identifies the “virtual router” in the LAN and is part of every BRRP advertisement packet that is sent by the current master. A value for this parameter is generated automatically when a new entry is created, but this value can be changed.</p> <p>Possible values are whole numbers between 1 and 255.</p>
Virtual Router State	<p>Defines the state of the virtual interface in the “virtual router”.</p> <p>Options are <i>up</i> and <i>down</i>. The state set here does not refer to the whole “virtual router”, but only to the participation of the virtual interface in the “virtual router”.</p> <p>The default value is <i>down</i>.</p> <p>Note that the parameters of the “virtual router” can only be configured if the interface is inactive in the “virtual router”. To deactivate an active “virtual router”, set the VIRTUAL ROUTER STATE to <i>down</i> and press SAVE. You can then return to the ADD/EDIT menu and change the parameters.</p>

Field	Description
Priority	<p>Defines the logical priority of the virtual interface in the “virtual router”. Possible values are between 1 and 255. The higher the value, the higher the priority.</p> <p>The value 255 defines that this virtual interface always functions as master as soon as it is active.</p> <p>Usually, the virtual interface with the highest priority functions as master. PRIORITY and PRE-EMPT MODE define the further roles between master and slave when a backup situation occurs.</p> <p>The default value is 100.</p>
Advertisement Interface	<p>Defines the interface via which the BRRP advertisement packets are sent and waited for.</p> <p>According to the configuration the respective physical interface (given that an IP address has been assigned) and all virtual interfaces with configured IP address, not being specified for BRRP only, are available.</p> <p>If BRIDGING = <i>enabled</i> on the physical interface, a respective virtual interface with the required IP address has to be configured for this interface to be able to send and receive BRRP advertisement packets.</p>
Virtual Interface	<p>Defines which interface is to participate in the “virtual router”. All virtual >> Ethernet interfaces tagged for BRRP can be selected.</p>
Master IP-Address	<p>Shows the >> IP address of VIRTUAL INTERFACE. This value cannot be edited.</p>
MAC Address	<p>Shows the >> MAC address of VIRTUAL INTERFACE. This value cannot be edited.</p>

Field	Description
Advertisement Interval	<p>Defines how often a BRRP advertisement packet is sent if the virtual interface is defined as master. Only the current master sends BRRP advertisements.</p> <p>Possible values are whole numbers between 1 and 255. The value is indicated in seconds and the default value is 1.</p> <p>An Advertisement Timer based on the Advertisement Interval runs in the router and an advertisement packet is sent when the timer expires.</p>
Master Down Interval	<p>The value entered here defines the number of BRRP advertisements that must fail before the backup assumes that the master is inactive and takes over the role of master.</p> <p>A Master Down Timer based on the Master Down Interval runs in the router; when this timer expires, the backup assumes that the master is not reachable if no advertisement has been received.</p> <p>The effective Master Down Interval corresponds to the time calculated from the number of expected but omitted BRRP advertisements, the Advertisement Interval and the so-called Skew Time, which adds a minimum time dependent on the priority of the virtual interface in the “virtual router” (the higher the priority, the shorter the time added, so that a backup with higher priority reacts before one with a low priority).</p> <p>Possible values are whole numbers between 1 and 255 and the default value is 3.</p>

Field	Description
Pre-empt Mode	<p>Defines whether a backup with higher priority has priority over a master with low priority.</p> <p>Possible values:</p> <ul style="list-style-type: none"> ■ <i>true</i> (default value): Activates the feature. ■ <i>false</i>: Deactivates the feature. <p>Note the following exception: If PRIORITY 255 is selected, the gateway with this priority certainly takes over the master role, i.e. the setting in Pre-empt Mode is not considered. You should therefore select a PRIORITY lower than 255 if you wish to use Pre-empt Mode.</p>
Authentication Type	<p>Defines the type of authentication used for exchanging the BRRP advertisement packets.</p> <p>Selection options:</p> <ul style="list-style-type: none"> ■ <i>No Authentication</i> (default value): No authentication is used. ■ <i>Plain Text Password</i>: BRRP advertisement packets are authenticated by a plain text password. All packets that cannot be authenticated are discarded. <p>(VRRP RFC and the Internet draft provide for the use of IP authentication headers. This option will be implemented later.)</p>
Authentication Key	<p>Only for AUTHENTICATION TYPE = <i>Plain Text Password</i>.</p> <p>The authentication key is entered here. Note that this is the same for all virtual interfaces participating in the “virtual router”.</p>

Table 3-1: **CONFIGURATION** menu fields

4 Monitoring Submenu

The **MONITORING** submenu is described below.

R3000W Setup Tool			Funkwerk Enterprise Communications GmbH		
[BRRP] [MONITOR]: Virtual Router Monitoring			MyGateway		
VrID	Prio	State	Interface	Master-IP-Addr	Errors
1	100	down	en0-1-1	0.0.0.0	0
2	100	down	en0-1-2	0.0.0.0	0
EXIT					

The **BRRP → MONITORING** menu displays a list of all "virtual routers".

The list contains the following data:

Column	Description
VrID	ID of the "virtual router"
Prio	Configured priority: ■ 255 = Master ■ <255 = Slave
State	The current state of the BRRP gateway in the "virtual router".
Interface	Interface within the "virtual router"
Master-IP-Addr	IP address of the virtual interface of the master.
Errors	Total sum of received defective packets.

Table 4-1: Virtual Router Monitoring List

Detailed statistical information about the individual “virtual routers” are displayed by positionning the cursor on the desired “virtual router” list entry and pressing the **Return** key.

R3000w Setup Tool		Funkwerk Enterprise Communications GmbH
[BRRP] [MONITOR] [DETAILS] : Virtual Router Details		MyGateway
Virtual Router ID	1	
Virtual Router State	backup	
Become Master	2	
Advertisements Received	23536	
Advertisement Interval Errors	0	
Version Errors	0	
Authentication Errors	0	
Authentication Type Mismatch	0	
Invalid Authentication Type	30	
Invalid Type Packets Received	0	
Packet Length Errors	0	
IP TTL Errors	0	
Checksum Errors	0	
EXIT		

The **MONITORING** menu consists of the following fields:

Field	Description
Virtual Router ID	Here you select the ID of the “virtual router” whose statistics you wish to see.
Virtual Router State	The current state of the BRRP gateway in the “virtual router”. This field can have the following values: <ul style="list-style-type: none"> ■ <i>initialize</i>: The BRRP gateway waits for a startup event. ■ <i>backup</i>: The BRRP gateway monitors the reachability of the master router. ■ <i>master</i>: The BRRP gateway forwards packets to ➤➤ IP addresses that are linked to this router.

Field	Description
Become Master	The total number of state transitions of the BRRP gateway to <i>master</i> .
Advertisements Received	The total number of BRRP advertisements received by BRRP gateway.
Advertisement Interval Errors	The total number of BRRP advertisement packets received whose advertisement interval differs from that configured on the local BRRP gateway.
Version Errors	The total number of BRRP packets received with unknown or unsupported version number.
Authentication Errors	The total number of BRRP packets received with wrong AUTHENTICATION KEY .
Authentication Type Mismatch	The total number of packets received in which the AUTHENTICATION TYPE is known, but not the same as the authentication type configured locally.
Invalid Authentication Type	The total number of packets received with a completely unknown authentication type.
Invalid Type Packets Received	The number of BRRP packets received by the “virtual router” with an invalid value in the ‘type’ field of the BRRP header. The correct value for ‘type’ is ‘1’ (‘advertisement’).
Packet Length Errors	The total number of packets received with a smaller packet length than the length specified in the BRRP header.
IP TTL Errors	The total number of BRRP packets received by the “virtual router” with IP TTL (Time-To-Live) not equal to 255.
Checksum Errors	The total number of BRRP packets received with an invalid BRRP checksum.

Table 4-2: **MONITORING** menu fields

Index: BRRP

A	Advertisement Interface	23
	Advertisement Interval	24
	Advertisement Interval Errors	29
	Advertisements Received	29
	Authentication Errors	29
	Authentication Key	25
	Authentication Type	25
	Authentication Type Mismatch	29
B	Backup	17
	Become Master	29
	BRRP states	15
C	Checksum Errors	29
I	Initialize	16
	Invalid Authentication Type	29
	Invalid Type Packets Received	29
	IP Address Owner	5
	IP TTL Errors	29
M	MAC address	6, 23
	Master	18
	Master Action	12
	Master Down Interval	24
	Master Interface	13
	Master Interface Protocol	11
	Master IP-Address	23
P	Packet Length Errors	29
	Pre-empt Mode	25
	Primary IP Address	5
	Priority	23

R	Redundant network environment	3
	RFC 2338	3
	Router redundancy procedure	3
S	Slave Admin Action	14
	Slave Interface	15
	Slave Interface Protocol	13
T	Task ID	10
V	Version Errors	29
	Virtual Interface	23
	Virtual Router	3, 5
	Virtual Router Backup	5
	Virtual Router ID	12, 15, 22, 28
	Virtual Router Master	5
	Virtual Router State	22, 28
	VRRP Advertisement	5
	VRRP Router	4
W	Watchdog Daemon	6, 9